

## A140 BT

1085L two door refrigerated cabinet -25 / -15°C

### functions

Temperature range	<b>-25 / -15°C</b>
Energy label	<b>D</b>
Climatic class	<b>5</b>

### technical data

Width (mm)	<b>1400</b>
Depth (mm)	<b>830</b>
Height (mm)	<b>2080</b>
Weight (kg)	<b>200</b>
Opening door depth 90° (mm)	<b>1460</b>
Capacity (L)	<b>1085</b>
Distance between runners (mm)	<b>55</b>
N° trays 2/1GN (535x650) or 600x800	<b>48</b>
Electric connection (V/~/Hz)	<b>230/1/50</b>
Electric power (W)	<b>910</b>
Max. absorbed current (A)	<b>4.4</b>
Cooling power (W)	<b>859</b>
Consumption (kWh/kg) ISO16825 (W24h)	<b>13.9</b>
Internal width (mm)	<b>1250</b>
Internal depth (mm)	<b>710</b>
Internal height (mm)	<b>1480</b>
Gross weight (kg)	<b>225</b>
Refrigerant type (gas)	<b>R452A</b>



### main features

- Stainless steel inside and outside.
- Moulded guide supports.
- 83 mm side insulation with CFC-free polyurethane.
- Openable instrument panel for easier periodic maintenance (condenser cleaning).
- Touch screen control.
- Cell interior with rounded corners for easy cleaning.
- 150 mm steel feet with adjustable height.
- Automatic defrosting with heater and dissipation of condensed water with hot gas.
- Self-locking hinged doors.
- Light and lock fitted as standard.
- Suitable to be placed on plinth.
- External single-block buffer unit with forced top down ventilation.



