

A140 TNN

1085L two door refrigerated cabinet -2 / +8°C

functions

Temperature range	-2 / +8°C
Energy label	D
Climatic class	5

technical data


Width (mm)	1400
Depth (mm)	830
Height (mm)	2080
Weight (kg)	191
Opening door depth 90° (mm)	1460
Capacity (L)	1085
Distance between runners (mm)	55
N° trays 2/1GN (535x650) or 600x800	48
Electric connection (V/~ /Hz)	230/1/50
Electric power (W)	470
Max. absorbed current (A)	1.96
Cooling power (W)	418
Consumption (kWh/kg) ISO16825 (W24h)	4.54
Internal width (mm)	1250
Internal depth (mm)	710
Internal height (mm)	1480
Gross weight (kg)	216
Refrigerant type (gas)	R134A



main features

- Stainless steel inside and outside.
- Moulded guide supports.
- 83 mm side insulation with CFC-free polyurethane.
- Openable instrument panel for easier periodic maintenance (condenser cleaning).
- Touch screen control.
- Cell interior with rounded corners for easy cleaning.
- 150 mm steel feet with adjustable height.
- Automatic defrosting with heater and dissipation of condensed water with hot gas.
- Self-locking hinged doors.
- Light and lock fitted as standard.
- Suitable to be placed on plinth.
- External single-block buffer unit with forced top down ventilation.





REV/MODIFICA	1	2	3	4	5	6	7	8	9	10	11	12
DATA												
DISSEG.												
VISTO												
DATA												
APPR												
SUT 70-140 FIANCHI STAMPATI												
6TDS0054												

THIS DRAWING IS THE PROPERTY OF ALL S.p.A. IT MUST NOT BE DISCLOSED, COPIED OR USED FOR PRODUCTION WITHOUT THEIR WRITTEN AUTHORIZATION