



	<b>WATER CONNECTION 3/4" GAS</b>
	<b>DRAIN PIPE Ø 32mm</b>
	<b>ELECTRICAL SUPPLY</b>

TECHNICAL DATA		STANDARD			
<b>EXTERNAL DIMENSIONS</b>					
width	1490 mm				
depth	885 mm				
height	1970 / 2310 mm				
WEIGHT	320 kg				
VOLTAGE	400V 3N 50Hz				
POWER EQUIRED	14800 W				
WATER HARDNESS	2-8 °F				
INLET WATER PRESSURE	200 - 400 kPa				
<b>CROCKERY DIMENSIONS</b>					
max. tray height	820 mm				
RACK DIMENSIONS	1350 x 725 mm				
RACK EQUIPMENT	1 x spatula basket - 1 x tray support - 1 x s/steel basket				
WASHING CYCLES (min)	1(3)	2(6)	3(9)	4(12)	
<b>WATER SUPPLY 55°C</b>					
rack/h <sup>(*)</sup> (1)	20	10	6	5	
<b>WATER SUPPLY 10°C</b>					
rack/h <sup>(*)</sup> (1)	20	10	6	5	
WATER CONSUMPTION / CYCLE	8.6 L				
BOILER CAPACITY	20 L				
BOILER HEATING ELEMENT	9000 W				
RINSING TEMPERATURE (SET)	85 °C				
TANK CAPACITY	120 L				
TANK HEATING ELEMENT	9000 W				
TANK TEMPERATURE (SET)	55 °C				
WASHING PUMP POWER	2900 W (810 L/min <sup>***</sup> ) x 2				
RINSING PUMP POWER	250 W (150 L/min <sup>***</sup> ) x 2				
DRAIN PUMP (optional)	190 W (120 L/min <sup>***</sup> )				
NOISE	71.9 dB(A)				

(\*) STANDARD THERMOSTOP

(\*\*\*) MAXIMUM FLOW RATE

<sup>1)</sup> In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash -cycle total timing might result longer than set.