



## PI-20

### STAINLESS STEEL CONSTRUCTION

- Side stirrers covered with silicon carbide abrasive (approved by NSF).
- ° Aluminium base plate lined with silicon carbide abrasive (approved by NSF)

- Construction in stainless steel.
- Lateral stirrers covered with silicon carbide abrasive (approved by NSF).
- ° Aluminium base plate lined with silicon carbide abrasive (approved by NSF), easily removable for cleaning purpose.
- Auto-drag of waste to the drain.
- Energy optimisation thanks to engine optimization.
- Lifiable transparent polycarbonate cover, complete with locking and safety device.
- Aluminium door with hermetic seal and safety device.
- Waterproof control board (IP65): Improved reliability against moisture and water splash.
- Water inlet system with non-return air break.
- Auxiliary contact for external electric valve.
- Timer 0-6min and continuous operation.

#### DEFAULT EQUIPMENT

#### OPTIONAL EQUIPMENT

- Stand.
- Filter with no-foam feature.

### TECHNICAL SPECIFICATIONS

Hourly production: 400 Kg / 480 Kg  
 Load capacity per programme: 20 Kg  
 Timer (min-max): 0' - 6'  
 Loading: 550 W

#### External dimensions

- Width: 433 mm
- Depth: 635 mm
- Height: 735 mm

#### external dimensions with support

- height with support: 433 mm
- depth with support: 638 mm
- height with support: 1155 mm

Net weight: 39 Kg

