



## PRODUCT ADVANTAGES

- **CUTLERY PREMIUM:** ensures up to 80 pieces of clean & shiny cutlery without polishing are produced each cycle. The program is selected automatically by the machine. Combine with Reverse Osmosis RO-S for optimum results.
- The innovative system creates the true multi-purpose machine by allowing it to be used for CUTLERY WASHING & DRYING, GLASS WASHING & DRYING, table water bottle washing (optional bottle wash kit required) & general washing
- **TOP-DRY:** integrated drying technology - no need for manual drying
- **VAPOSTOP<sup>2</sup>:** allows door opening without steam cloud. Also prevents steam escape during the drying phase
- **Self-cleaning wash system:** The combined wash & rinse system features innovative self-cleaning of the wash arms with every cycle. This saves time & ensures perfect cleaning
- **SmartConnect app:** controlling your warewash operation with smart technology: status & messages, usage & operating costs, hygiene & service
- **Eco programme:** switchable steam rinse cycle reduces fresh-water consumption to 0.8 l. Saving of up to 60 % water and chemicals
- **VISIOTRONIC-TOUCH control:** colour touchscreen (displays text & graphic) with single-button control & remaining cycle time indication
- **SENSO-ACTIVE resource management:** adjusts the rinse cycle volume to ensure the best results
- **Optional 2IN1 double rack system:** two racks can be washed in a single wash cycle. Thanks to the optimum use of the entire wash chamber the performance of the machine can be doubled
- **CLIP-IN wash and rinse system:** easy removal without any tools
- **Intelligent data documentation:** auto recording of important operational data & consumptions & indication on the display
- **USB-interface:** download operational data in a protocol form via USB
- **GENIUS-X<sup>2</sup> fine filter system:** advanced filter system with pre-wash function reduces detergent consumption up to 35 %
- **Interlocked strainer:** prevents operation without tank strainer
- **Optional refill signal:** monitors levels of external chemical HOBART containers
- **Hygiene programme (in combination with Hygiene-Tab INTENSIV)** for removal of calcium carbonate and other deposits from wash chamber
- **Thermolabel 71 °C:** default temperatures setting acc. European DIN can be switched by operator to a higher thermolabel setting
- **WATERMARK APPROVED**

## TECHNICAL DATA

Cycle times*	1. 80sec 2. 150sec 3. 170sec 4. 270sec
CUTLERY PREMIUM	
Water consumption Standard washing CUTLERY PREMIUM	0.8 l/rack ECO Cycle 3.4 l/rack
Tank capacity	10.6 l
Tank heating	0.8 kW
Power supply	415 / 50 / 3N (240 / 50 / 1)
Booster loading Standard Alternative	6.2 kW 4.1 kW
Total loading Standard Alternative	7.7 kW   3 x 15 A 5.6 kW   25 A
Wash pump	0.6 kW   350 l/min
Rack size	500 x 500
Loading height	425 mm
Noise level	60.5 dB (A)
Weight (gross / net)	77 / 67 kg

\* Thermostat guarantees required temperatures with cold water and / or 240 V connection, the actual cycle times extend accordingly.  
For machine protection the water hardness should not exceed 3°dH, if higher we recommend using an integrated water softener or an external water softener of the product line HYDROLINE PROTECT.

## CONNECTIONS

① Drain hose	2,000 mm   ID20/OD25
Reverse Osmosis unit (RO-S)	Independent gravity waste to tundish
② Supply hose	2,000 mm   R 3/4"
Required flow rate	5 l/min
Flow pressure	0.5 (0.8 with softener)- 6 bar
Max. supply water temperature	60 °C 35 °C With RO-S
③ Power cord	2,000 mm
Supply hose for	
④ Detergent	2,500 mm
⑤ Rinse aid	2,500 mm

