


| Glasswasher Comparison | | |
|---|--|--|
|  | CURRENT - SMEG - Model: UG405DMAUS | NEW - SMEG - Model: SPG405MAU |
| Washing Cycle Durations | 90 / 150 / 240 Seconds | 90 / 150 / 240 Seconds |
| Machine Dimensions | 440mm Wide / 530mm Deep & 710mm High | 440mm Wide / 530mm Deep - <i>Note: Below the door the Depth is 555mm</i> & Machine Height is 695mm |
| Drain Pump | Yes | Yes |
| Rinse Pump | Yes | Yes |
| Thermostop System to Ensure Correct Rinse Temperature | Yes | Yes |
| Basket Size | 400mm x 400mm & 17" x 14" baskets accepted | 400mm x 400mm & 17" x 14" baskets accepted |
| Door Clearance | 330mm | 330mm |
| Door/Hood Structure | Fully Insulated Door and Single Skin sides | Fully Insulated Door and Single Skin sides |
| Washtank Volume in Litres | 8 | 8 |
| Boiler Volume in Litres | 4 | 4 |
| Boiler Heater Element | 2,700 Watts | 2,700 Watts |
| Soft Start Wash Pump | Yes | Yes |
| Tank Temperature and Washing Temperature | 60 Degrees Celcius | 60 Degrees Celcius |
| High Temperature Rinse | Yes & Rinses at 85 Degrees Celcius | Yes & Rinses at 85 Degrees Celcius |
| Smart Drain System (Prior to Starting to Rinse with clean water - The Smart Drain System partially empties water in the wash tank by Draining the Dirtiest water from the bottom of the wash tank and clean water is introduced from the Rinse Water) | Yes | Yes |
| Automatic Self Cleaning Cycle | Yes | Yes |
| Self Diagnostic System with Error Codes | Yes | Yes |
| Adjustable Peristaltic Pumps for Detergent & Rinse Aid | Yes Standard | Yes Standard |
| Electronic Controls | Yes | Yes |
| Voltage | 15amp Single Phase Supply with Plug | 15amp Single Phase Supply with Plug |
| Smeg Professional Warranty | Two Years Parts & Labor Warranty | Two Years Parts & Labor Warranty |